

SAFETY DATA SHEET

United States		
Section 1. Identification Product name	HiTrap™ SP FF 1	ml, 5 x 1 ml
Catalogue Number	17505401	$\begin{array}{c} \begin{array}{c} \\ \end{array} \\ \end{array} \\ \end{array} \\ \begin{array}{c} \\ \end{array} \\ \end{array} \\ \end{array} \\ \begin{array}{c} \\ \end{array} \\ \end{array} \\ \end{array} \\ \begin{array}{c} \\ \end{array} \\ \end{array} \\ \end{array} \\ \end{array} \\ \begin{array}{c} \\ \end{array} \\ \end{array} \\ \end{array} \\ \end{array} \\ \begin{array}{c} \\ \end{array} \\ $
Other means of identification Product type	Not available. Liquid.	
Identified uses Laboratory chemicals Liquid chromatography. Scientific research and developm	ubstance or mixture and uses advised ent chemistry. Scientific research and deve	
Supplier	Cytiva Amersham Place Little Chalfont Buckinghamshire HP7 9NA United Kingdom +44 0800 515 313	Cytiva USA 100 Results Way Marlborough, MA 01752 1-800-526-3593
In case of emergency	INFOTRAC - 24 Hour number: 1-800-5 Outside of the United States, call 24 H	335-5053 our number: 001-352-323-3500 (Call Collect)
Section 2. Hazards ident	ification	
OSHA/HCS status	This material is considered hazardous 1910.1200).	by the OSHA Hazard Communication Standard (29 CFR
Classification of the substance or mixture	FLAMMABLE LIQUIDS - Category 3	
<u>GHS label elements</u> Hazard pictograms		
Signal word	Warning	
Hazard statements	Flammable liquid and vapor.	
Precautionary statements		
Prevention	clothing: Recommended: lab coat. We side-shields. Keep away from heat, ho No smoking. Use explosion-proof elec tools. Take action to prevent static dis	eakthrough time): butyl rubber, neoprene. Wear protective ar eye or face protection: Recommended: safety glasses with ot surfaces, sparks, open flames and other ignition sources. strical, ventilating or lighting equipment. Use non-sparking charges. Keep container tightly closed.
Response		ately all contaminated clothing. Rinse skin with water.
Storage Disposal	Store in a well-ventilated place. Keep of	cool. ccordance with all local, regional, national and international
Hazards not otherwise classified	regulations. None known.	oordanoo wiin an iooar, regional, nauonai anu international

Article Number :

9517505401

17505401

Page: 1/8 Validation date 4 October 2023

Section 3. Composition/information on ingredients

Substance/mixture Other means of identification	Mixture Not available.		
CAS number/other identifiers CAS number	Not applicable.		
Ingredient name ethanol		% 14 - 19	CAS number 64-17-5

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first a	aid measures
Eye contact	Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Get medical attention if irritation occurs.
Inhalation	Remove victim to fresh air and keep at rest in a position comfortable for breathing.
Skin contact	Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Get
Ingestion	medical attention if symptoms occur. Wash out mouth with water. If material has been swallowed and the exposed person is conscious,
ingestion	give small quantities of water to drink. Do not induce vomiting unless directed to do so by medical personnel.
Most important symptoms/effe	cts, acute and delayed
Potential acute health effects	
Eye contact	No known significant effects or critical hazards.
Inhalation	No known significant effects or critical hazards.
Skin contact	No known significant effects or critical hazards.
Ingestion	No known significant effects or critical hazards.
Over-exposure signs/sympto	<u>ms</u>
Eye contact	No specific data.
Inhalation	No specific data.
Skin contact	No specific data.
Ingestion	No specific data.
Indication of immediate medica	al attention and special treatment needed, if necessary
Notes to physician	Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
Specific treatments	No specific treatment.
Protection of first-aiders	No action shall be taken involving any personal risk or without suitable training.
See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media

Suitable extinguishing media	Use dry chemical, CO ₂ , water spray (fog) or foam.
Unsuitable extinguishing media	Do not use water jet.
Specific hazards arising from the chemical	Flammable liquid and vapor. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion.
Hazardous thermal decomposition products	Decomposition products may include the following materials: carbon dioxide carbon monoxide metal oxide/oxides
Special protective actions for fire-fighters	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.
Special protective equipment for fire-fighters	Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Put on appropriate personal protective equipment.			
For emergency responders	If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".			
Environmental precautions	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).			
Methods and materials for contai	inment and cleaning up			
Small spill	Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion- proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.			
Large spill	Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion- proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.			

Section 7. Handling and storage

Precautions for safe handling	
Protective measures	Put on appropriate personal protective equipment (see Section 8). Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing vapor or mist. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. To avoid fire or explosion, dissipate static electricity during transfer by grounding and bonding containers and equipment before transferring material. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
Conditions for safe storage, including any incompatibilities	Store between the following temperatures: 4 to 30°C (39.2 to 86°F). Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits ethanol

ACGIH TLV (United States, 1/2022). Notes: 1996 Adoption Refers to Appendix A -- Carcinogens. STEL: 1000 ppm 15 minutes. NIOSH REL (United States, 10/2020). Notes: TWA: 1900 mg/m³ 10 hours. NIOSH REL (United States, 10/2020). TWA: 1000 ppm 10 hours. OSHA PEL (United States, 5/2018). TWA: 1900 mg/m³ 8 hours. TWA: 1900 ppm 8 hours. OSHA PEL 1989 (United States, 3/1989). TWA: 1900 mg/m³ 8 hours. TWA: 1900 mg/m³ 8 hours.

Biological exposure indices

No exposure indices known.

Appropriate engineering controls Environmental exposure controls	Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment. Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
Individual protection measures	
Hygiene measures	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection	Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields. Recommended: safety glasses with side-shields
Skin protection	
Hand protection	Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. 1 - 4 hours (breakthrough time): butyl rubber, neoprene
Body protection	Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves. Recommended: lab coat
Other skin protection	Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use. Recommended: A respirator is not needed under normal and intended conditions of product use.
Personal protective equipment (Pictograms)	

Section 9. Physical and chemical properties

Appearance

	Ingredient name	mm Hg	kPa	Method	mm Hg	kPa	Method	
		Va	por Press	ure at 20°C	Va	por pres	sure at 50°C	
Vapor pressure	Not available.							
Lower and upper explosive (flammable) limits	Not available.							
Flammability	Not available.							
Evaporation rate	Not available.							
Burning rate	Not applicable.							
Burning time	Not applicable.							
Flash point	Closed cup: 38 to	43°C (100.4 to	o 109.4°F)					
Boiling point, initial boiling point, and boiling range	Not available.							
Melting point/freezing point	Not available.							
рН	5.5 to 8.5 [Conc. (9	% w/w): 100%]					
Odor threshold	180 ppm							
Odor	Alcohol-like. [Sligh	t]						
Color	White. White to ye	llowish.						
Physical state	Liquid.							
Appearance								

, -						
	ethanol	42.95	5.7			
	water	23.8	3.2			
	Agarose	0	0			
	sodium acetate	0	0			
Relative vapor density Relative density Solubility(ies)	Not available. Not available.					
Colubility(ICS)	Media		Result			
	cold water hot water		Easily soluble Easily soluble			
Solubility in water	Not available.					
Miscible with water	Yes.					
Partition coefficient: n-octan water	ol/ Not applicable.					
Auto-ignition temperature	Not available.					
	Ingredient name		°C	°F	Method	
	ethanol		455	851	DIN 51794	
	sodium acetate		607.22	1125		
Decomposition temperature	Not available.					
SADT	Not available.					
Viscosity	Not available.					
Flow time (ISO 2431)	Not available.					
Particle characteristics						
Median particle size	Not applicable.					
Section 10. Stability a	nd reactivity					
Reactivity Chemical stability Possibility of hazardous	No specific test dat The product is stab Under normal cond	le.	·		ct or its ingredients. ns will not occur.	

Chemical stability	The product is stable.
Possibility of hazardous reactions	Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition.
Incompatible materials	Reactive or incompatible with the following materials: oxidizing materials
Hazardous decomposition products	Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity				
Product/ingredient name	Result	Species	Dose	Exposure
ethanol	LC50 Inhalation Vapor	Rat	124700 mg/m ³	4 hours
Irritation/Corrosion Not available.				
Conclusion/Summary				
Skin <u>Sensitization</u> Not available.	Repeated exposure may cause skin dr	yness or cracking.		
<u>Mutagenicity</u> Not available.				
Carcinogenicity Not available.				
Reproductive toxicity Not available.				
<u>Teratogenicity</u> Not available.				

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard

Not available.

Information on the likely routes Routes of entry anticipated: Oral, Dermal, Inhalation, Eyes. of exposure

Potential acute health effects					
Eye contact	No known significant effects or critical hazards.				
Inhalation	No known significant effects or critical hazards.				
Skin contact	No known significant effects or critical haz	zards.			
Ingestion	No known significant effects or critical haz	zards.			
Symptoms related to the physica	I, chemical and toxicological characteris	stics			
Eye contact	No specific data.				
Inhalation	No specific data.				
Skin contact	No specific data.				
Ingestion	No specific data.				
Delayed and immediate effects a	nd also chronic effects from short and lo	ong term expo	<u>sure</u>		
Short term exposure					
Potential immediate effects	Not available.				
Potential delayed effects	Not available.				
Long term exposure					
Potential immediate effects	Not available.				
Potential delayed effects	Not available.				
Potential chronic health effects					
Not available.					
General	No known significant effects or critical haz	zards.			
Carcinogenicity	No known significant effects or critical haz	zards.			
Mutagenicity	No known significant effects or critical haz	zards.			
Reproductive toxicity	No known significant effects or critical haz	zards.			
Numerical measures of toxicity					
Acute toxicity estimates					
Product/ingredient name	Oral (mg/kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapors) (mg/l)	

mists) (mg/ I) Media in 20% EtOH + 0.2M NaAc (Sepharose only) (4-30) -356530.0 N/A N/A N/A N/A GROUP ethanol 7000 N/A N/A N/A 124.7 Other information Adverse symptoms include the following: kidney abnormalities, liver abnormalities Adverse symptoms may include the following: central nervous system depression

Section 12. Ecological information

<u>Toxicity</u>					
Product/ingredient name	Result		Species		Exposure
ethanol	Acute EC50 3306 mg/l Marine water		Algae - <i>Ulva pertusa</i>		96 hours
	Acute EC50 1074 n	ng/l Fresh water	Crustaceans - Cypris sul	bglobosa	48 hours
	Acute EC50 9.3 mg	/I Fresh water	Daphnia - Daphnia magr	na	48 hours
	Acute LC50 11000	000 μg/l Marine water	Fish - Alburnus alburnus		96 hours
	Chronic NOEC 4.99	95 mg/l Marine water	Algae - Ulva pertusa		96 hours
	Chronic NOEC 100	ul/L Fresh water	Daphnia - Daphnia magr	na - Neonate	21 days
Persistence and degradability					
Product/ingredient name	Test	Result	Dose	Inoc	ulum
ethanol	-	100 % - Readily - 20 day	s -	-	
Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability		ity
ethanol	-	-	R	eadily	

Bioaccumulative potential

Article Number :



Page: 6/8 Validation date 4 October 2023

Inhalation

(dusts and

HiTrap™ SP FF 1 ml, 5 x 1 ml Product/ingredient name	LogPow	BCF	Potential
ethanol	-0.35	0.66	Low
Mobility in soil			
Soil/water partition coefficient (K oc)	Not available.		
Other adverse effects	No known signific	ant effects or critical hazards.	
Section 13. Disposal co	nsiderations		
Disposal methods	product, solutions environmental pro- requirements. Di contractor. Wast requirements of a or landfill should must be disposed have not been cle Vapor from produ container. Do no	Il authorities with jurisdiction. Waste pa only be considered when recycling is no I of in a safe way. Care should be taken eaned or rinsed out. Empty containers o ict residues may create a highly flammal t cut, weld or grind used containers unle	s comply with the requirements of and any regional local authority ducts via a licensed waste disposal b the sewer unless fully compliant with the ackaging should be recycled. Incineration t feasible. This material and its container o when handling emptied containers that or liners may retain some product residues. ble or explosive atmosphere inside the
Waste stream	Code: D001 Classification: Igr	nitability	
Section 14. Transport in	formation		
Product is not regulated as da	ngerous goods for	transport.	
Section 15. Regulatory i	nformation		
U.S. Federal regulations	TSCA 8(a) CDR I	Exempt/Partial exemption: Not determi	ined
Clean Air Act Section 112(b) Ha (HAPs) Clean Air Act Section 602 Class Clean Air Act Section 602 Class DEA List I Chemicals (Precurso DEA List II Chemicals (Essentia	l Substances Il Substances r Chemicals)	ants Not listed Not listed Not listed Not listed Not listed	
<u>SARA 302/304</u>			
Composition/information on in	<u>igredients</u>		
No products were found.			
SARA 304 RQ	Not applicable.		
<u>SARA 311/312</u>			
Classification		QUIDS - Category 3	
Composition/information on in	<u> </u>		
Name ethanol	% 14 - 19	Classification FLAMMABLE LIQUIDS - Cated	nory 2
State regulations	The following con	anonanta ara liatadi ETUVLALCOLO	
Massachusetts New York	•	nponents are listed: ETHYL ALCOHOL ponents are listed.	
New Jersey		nponents are listed: ETHYL ALCOHOL	
Pennsylvania	The following con	nponents are listed: ETHANOL	
<u>California Prop. 65</u>			
This product does not requi	re a Safe Harbor wa	arning under California Prop. 65.	
International regulations			
Chemical Weapon Convention	List Schedules I, I	I & III Chemicals	
Not listed.			
Montreal Protocol			
Not listed.			
		U	
Stockholm Convention on Per-	<u>sistent Organic Po</u>	llutants	



HiTrap™ SP FF 1 ml, 5 x 1 ml		17505
Rotterdam Convention on Prior	r Informed Consent (PIC)	
Not listed.		
UNECE Aarhus Protocol on PO	Ps and Heavy Metals	
Not listed.		
Inventory list		
United States	Not determined.	
Canada inventory	All components are listed	l or exempted
	•	
Section 16. Other inform	ation	
National Fire Protection Associa	<u>tion (U.S.A.)</u>	
	F la	ammability
	Health 1 0	Instability/Reactivity
	Sr	pecial hazards
Procedure used to derive the cla	ssification	
	fication	Justification
FLAMMABLE LIQUIDS - Categor		On basis of test data
History		
Date of printing	10/4/2023	
Date of issue/Date of revision	10/4/2023	
Date of previous issue	2/9/2023	
Version	9	
	sds_author@cytiva.com	
Key to abbreviations	ATE = Acute Toxicity Est	
	BCF = Bioconcentration	⊢actor zed System of Classification and Labelling of Chemicals
	IATA = International Air 1	
	IBC = Intermediate Bulk	
	IMDG = International Ma	ritime Dangerous Goods ie octanol/water partition coefficient
		Convention for the Prevention of Pollution From Ships, 1973 as modifie
		("Marpol" = marine pollution)
	N/A = Not available UN = United Nations	
References	Not available.	
Indicates information	ation that has changed from	n previously issued version.
	alon that has onanged from	

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

